



TDCJ Risk Management's Training Circular

Volume 13 Issue 11

Risk Management Issues

November 2013



November Hazard Communication Standard



OSHA revised its Hazard Communication Standard (HCS) to align with the United Nations' Globally Harmonized System of Classification and Labeling of Chemicals (GHS) and published it in the Federal Register in March 2012 (77 FR 17574). Two significant changes contained in the revised standard require the use of new labeling elements and a standardized format for Safety Data Sheets (SDSs), formerly known as Material Safety Data Sheets (MSDSs). The new label ele-

ments and SDS requirements will improve worker understanding of the hazards associated with the chemicals in their workplace.

Labeling Requirements

The following information would be seen on the new labels:

Product identifier: how the hazardous chemical is identified. This can be (but is not limited to) the chemical name, code number or batch

number. The manufacturer, importer or distributor can decide the appropriate product identifier. The same product identifier must be both on the label and in Section 1 of the SDS (Identification).

Signal word: used to indicate the relative level of severity of hazard and alert the reader to a potential hazard on the label. There are only two signal words, "Danger" and "Warning." Within a specific hazard class, "Danger" is used for the more severe hazards and "Warning" is used for the less severe hazards. There will only be one signal word on the label no matter how many hazards a chemical may have. If one of the hazards warrants a "Danger" signal word and another warrants the signal word "Warning," then only "Danger" should appear on the label.

SAMPLE LABEL

CODE _____ Product Name _____	} Product Identifier	Hazard Pictograms 		
Company Name _____ Street Address _____ City _____ State _____ Postal Code _____ Country _____ Emergency Phone Number _____			} Supplier Identification	
Keep container tightly closed. Store in a cool, well-ventilated place that is locked. Keep away from heat/sparks/open flame. No smoking. Only use non-sparking tools. Use explosion-proof electrical equipment. Take precautionary measures against static discharge. Ground and bond container and receiving equipment. Do not breathe vapors. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Dispose of in accordance with local, regional, national, international regulations as specified.	} Precautionary Statements	Signal Word Danger		
			In Case of Fire: use dry chemical (BC) or Carbon Dioxide (CO ₂) fire extinguisher to extinguish.	} Hazard Statements Highly flammable liquid and vapor. May cause liver and kidney damage.
First Aid If exposed call Poison Center. If on skin (or hair): Take off immediately any contaminated clothing. Rinse skin with water.				

Pictogram: OSHA has designated eight pictograms under this standard for application to a hazard category.

Hazard statement(s): describe the nature of the hazard (s) of a chemical, including where appropriate, the degree of hazard. For example: "Causes damage to kidneys through prolonged or repeated exposure when absorbed through the skin." All of the applicable hazard statements must appear on the label. Hazard statements may be combined where appropriate to reduce redundancies and improve readability. The hazard statements are specific to the hazard classification categories, and chemical users should always see the same statement for the same hazards, no matter what the chemical is or who produces it.

Precautionary statement(s): means a phrase that describes recommended measures that should be taken to minimize or prevent adverse effects resulting from exposure to a hazardous chemical or improper storage or handling.

Name, address and phone number of the chemical manufacturer, distributor, or importer

Pictograms

The Hazard Communication Standard will require pictograms on labels to alert users of the chemical hazards to which they may be exposed. Each pictogram consists of a


symbol on a white background framed within a red border and represents a distinct hazard (s). The pictogram on the label is determined by the chemical hazard classification. A square red frame set at a point without a hazard symbol is not permitted on the label. Below are examples of pictograms to be used on the labels:

Gas Cylinder



- Gases Under Pressure

Health Hazard



- Carcinogen
- Mutagenicity
- Reproductive Toxicity
- Respiratory Sensitizer
- Target Organ Toxicity
- Aspiration Toxicity

Flame



- Flammables
- Pyrophorics
- Self-Heating
- Emits Flammable Gas
- Self-Reactives
- Organic Peroxides


Exclamation Mark




- Irritant (skin and eye)
- Skin Sensitizer
- Acute Toxicity (harmful)
- Narcotic Effects
- Respiratory Tract Irritant
- Hazardous to Ozone Layer (Non-Mandatory)

Corrosion


- Skin Corrosion/Burns
- Eye Damage
- Corrosive to Metals

Exploding Bomb

- Explosives
- Self-Reactives
- Organic Peroxides

Flame Over Circle

- Oxidizers

**Environment
(Non-Mandatory)**

- Aquatic Toxicity

Skull and Crossbones

- Acute Toxicity (fatal or toxic)

Safety Data Sheets (SDS)

The Hazard Communication Standard (HCS) requires chemical manufacturers, distributors, or importers to provide Safety Data Sheets (SDSs) (formerly known as Material Safety Data Sheets or MSDSs) to communicate the hazards of hazardous chemical products. As of June 1,

2015, the HCS will require new SDSs to be in a uniform format, and include the section numbers, the headings, and associated information under the headings below:

Section 1, Identification includes product identifier; manufacturer or distributor name, address, phone number; emergency phone number; recommended use; restrictions on use.

Section 2, Hazard(s) identification includes all hazards regarding the chemical; required label elements.

Section 3, Composition/information on ingredients includes information on chemical ingredients; trade secret claims.

Section 4, First-aid measures includes important symptoms/effects, acute, delayed; required treatment.

Section 5, Fire-fighting measures lists suitable extinguishing techniques, equipment; chemical hazards from fire.

Section 6, Accidental release measures lists emergency procedures; protective equipment; proper methods of containment and cleanup.

Section 7, Handling and storage lists precautions for safe handling and storage, including incompatibilities.

Section 8, Exposure controls/ personal protection lists OSHA's Permissible Exposure Limits (PELs); Threshold Limit Values (TLVs); appropriate engineering controls; personal protective equipment (PPE).

Section 9, Physical and chemical properties lists the chemical's characteristics.

Section 10, Stability and reactivity lists chemical stability and possibility of hazardous reactions.

Section 11, Toxicological information includes routes of exposure; related symptoms, acute and chronic effects; numerical measures of toxicity.

Section 12, Ecological information*

Section 13, Disposal considerations*

Section 14, Transport information*

Section 15, Regulatory information*

Section 16, Other information, includes the date of preparation or last revision.

*Note: Since other Agencies regulate this information, OSHA will not be enforcing Sections 12 through 15(29 CFR 1910.1200(g)(2)).

GHS vs NFPA 704

This new standardized labeling will replace the commonly known National Fire Protection Association (NFPA) 704 diamond. There are significant differences between the Hazard Communication Standard Globally Harmonized System (GHS) and NFPA hazard ratings. NFPA and GHS hazard identification numbers are used to rank hazards based upon their seriousness. Those rankings occurring under GHS are called Hazard Categories, with five indicating the lowest hazard and one indicating the most severe. The NFPA on the other hand also uses numbers to indicate hazard severity only in their systems, the maximum number four represents the most severe hazard and zero representing no hazard. Below is a summarization of the change in the hazard ranking system.

- NFPA hazard ranking
 - Ranked **0- 4; 4 being HIGH hazard.**
 - The new GHS hazard ranking Categories ranking in order of **1 – 5; 5 being a LOW hazard**

Change May Start Now

Even though the labeling and SDS requirements will not be required to fully implemented until June 1, 2015, some suppliers will use GHS labels much sooner – therefore, it is imperative to ensure employ-

ees are trained in the new labeling and SDS structure.

References

Occupational Safety and Health Administration (OSHA)
www.osha.gov



Training Circular
TDCJ Risk Management Department
Volume 13 Issue 11
November 2013

Oscar Mendoza
Director, Administrative
Review and Risk Management

Robert C. Warren
Risk Management Specialist V
Risk Management

The *Training Circular*, a publication of the TDCJ Risk Management Department, is published monthly in an effort to promote and enhance risk management awareness on issues relating to TDCJ employees. Design and layout of the Training Circular is performed by Robert C. Warren, Risk Management. Comments, suggestions and safety related items are welcome. Send suggestions to:

Robert C. Warren
Risk Management Department
1060 Hwy 190 East
Huntsville, Texas 77340
or,
robert.c.warren@tdcj.texas.gov

All items received become property of the Risk Management Department unless otherwise agreed and are subject to be rewritten for length and clarity. Permission is hereby granted to reprint articles, provided source is cited.